

ADVANTAGE HIGH TEMP TACKY RED #2

OVERVIEW

ADVANTAGE HIGH TEMP TACKY RED #2 is a high temperature, semi-synthetic, lithium complex based grease containing extreme pressure and special additives for increased adhesion and resistance to water washout. This grease meets ASTM D-4950 service classification.

FEATURES & BENEFITS

ADVANTAGE HIGH TEMP TACKY RED #2 has been formulated with semi-synthetic materials for outstanding high temperature and low temperature performance that provides excellent protection against wear, rust and corrosion. Its excellent thermal stability and oxidation resistance and low traction coefficient improves mechanical life and reduces energy consumption. ADVANTAGE HIGH TEMP TACKY RED #2 makes an outstanding general purpose automotive and heavy duty vehicle grease, as well as an industrial grease, and is designed for year round usage.

APPLICATIONS

ADVANTAGE HIGH TEMP TACKY RED #2 is designed for automotive wheel bearings, disc brakes, truck & bus lubrication, agricultural equipment, and multiple industrial applications.

TYPICAL PROPERTIES

Product Code	940
NLGI Consistency	#2
Viscosity, cSt @ 40°C	322
Viscosity, cSt @ 100 °C	29.2
Viscosity Index	124
Percent Soap	10.3
Rust Prevention	Pass
Oxidation Stability	3
Penetration 60XX	280
Soap Type	Lithium Complex
Dropping Point, °F	550°F
Timken EP	70
Load Wear Index	40
Weld Point	400
Color	Red